

# MOBILO LED CCT

SLI043040CCT\_PW

MOBILO LED 6.5W CCT 230V 36DEG. IP20 F1105x35MM BLACK ROUND

CCT



|                           |                      |                    |                             |
|---------------------------|----------------------|--------------------|-----------------------------|
| Power                     | <b>6,5 W</b>         | Voltage            | <b>230 V</b>                |
| Luminous flux*            | <b>850 lm (360°)</b> | Colour temperature | <b>2700 / 4000 / 6000 K</b> |
| Colour of light           | <b>CCT</b>           | Beam angle         | <b>36 °</b>                 |
| Degree of protection (IP) | <b>IP20</b>          |                    |                             |

## Technical data

|                              |                                                        |
|------------------------------|--------------------------------------------------------|
| Code                         | SLI043040CCT_PW                                        |
| Power                        | 6,5 W                                                  |
| Nominal current              | 52 mA                                                  |
| Voltage                      | 230 V                                                  |
| Energy consumption           | 7 kWh/1000h                                            |
| Frequency                    | 50HZ Hz                                                |
| Protection class             | II                                                     |
| Power factor                 | 0,5                                                    |
| Useful luminous flux*        | 850 lm (360°)                                          |
| Luminous flux**              | 800 lm (360°)                                          |
| Lamp efficacy                | 130 lm/W                                               |
| Luminous intensity           | 1300 cd                                                |
| Colour temperature           | 2700 / 4000 / 6000 K                                   |
| Colour of light              | CCT                                                    |
| Beam angle                   | 36 °                                                   |
| RA                           | 80                                                     |
| Light source included        | Yes                                                    |
| Uniformity of color SDCM max | 5                                                      |
| Dimmable                     | No                                                     |
| Working temperature range    | -20 / +40 °                                            |
| Warranty                     | 2 years                                                |
| Lifespan                     | 17000 h                                                |
| Housing material             | PC+PS                                                  |
| Degree of protection (IP)    | IP20                                                   |
| Colour                       | Black                                                  |
| Dimension (AxBxC)            | 105x35 mm                                              |
| Mounting hole                | 90 mm                                                  |
| For use                      | Inside                                                 |
| Assembly method              | Recessed                                               |
| Application                  | INT                                                    |
| Made in                      | PRC                                                    |
| Other                        | Light color change function<br>2700K / 4000K / 6000K , |

## Logistics data

|                       |         |
|-----------------------|---------|
| Bulk packaging        | 20 pcs. |
| Gross weight (1 pcs.) | 0.29 kg |

## Related documents

 User manual Declaration of Conformity